



FABRICANTES DE
MOLINOS DE CAFÉ

MANUFACTURERS
OF COFFEE GRINDERS

Molino de café profesional
para todo tipo de cafés

Professional coffee grinder
for all types of coffee.

BRASIL ABS


COLLECTION CLASSIC

TECHNICAL CHARACTERISTICS 0-500gr/6' Max 2Kg

Voltage: 230V / 220V / 110V
Frequency: 50Hz / 60Hz
Phases: 1(monophase)
RPM: 1.300 / 1.600
Current: 1,4A / 3A
Capacitor: 9nf / 40nf
Power: 0,12 Hp / 275W
Protection rating: IP21
Motor supplied with thermal protector
Maximum operating time: 30 min.
Tempered steel grinding wheel (62HRC) ø 60mm
Lifespan of grinding wheels: 500kg
Hopper capacity: 1kg
Doser capacity: 300g
Doser regulation: 5/12g
Doser lever: right/left
Stop/start standard version: manual
Optional: automatic start
Dimensions width x length x height: 210x380x470mm
Weight: 8 kg
Air noise: 77dB
<i>Diseñado bajo directiva 89/392 CE.</i>



Grinding blades in tempered steel
(62HRC) ø 60mm.



GREY DARK GREY BLACK PURPLE



MAIN ATTRIBUTES

Hopper (1kg) made of unbreakable and non-deformable material (co.polyester), with fast lock system and self-levelling when off the coffee grinder, with the possibility of cleaning in a dishwasher at 90 °C. Micrometric regulation of the coffee grind using a regulatory pawl. New expulsion system for the ground coffee (always leaving the grinding cavity clean when the coffee grinder stops). Bodywork manufactured in anti-scratch material, in a single piece (less vibrations, more robustness). With ventilation system (internal air inlet and outlet). Large tray integrated into the body, ready to take knocks (portafilter). Single-bodied, hermetically sealed doser without aroma loss, vibrationless and made of unbreakable material. Ergonomic handle. Universal coffee tamper (rotatable). Doser fitted with gasket-saver (portafilter positioner). Hardened steel grinding blades (62/65HRC) 60mm in diameter.

Optional: Left- or right-handed doser lever. Coffee counter. Optional personalisation system with chrome plates on the doser and on the rear of the bodywork. Automatic stop/start every two cups (depending on filling doser).

