

EVERPURE° MR-600 REPLACEMENT CARTRIDGE

MINERAL REDUCTION CARTRIDGE

MR-600 Replacement Cartridge: EV9627-13



APPLICATIONS

Coffee

Espresso

Reconstitution

Ice

Flash and conventional steamers

Combi ovens

Multiple applications

FEATURES • BENEFITS

Mineral reduction cartridge for high TDS waters

Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

A reduction in Total Dissolved Solids (TDS) makes the water less likely to impart undesirable tastes in beverages, sauces, soups and other food products

Improves equipment life and performance by removing at least 90%+ of all dissolved solids using Reverse Osmosis Separation Technology

Especially useful on steamers, warmers, steam boilers and other evaporative equipment that are not emptied each day

Heating surfaces maintain peak heat transfer efficiency, reducing cycle times and energy consumption

Limits limescale buildup, which can cause excessive machine downtime and maintenance costs

INSTALLATION TIPS

Install vertically with cartridge hanging down

Allow 2-1/2" (6.35 cm) clearance below the cartridge for easy cartridge replacement

Use piping materials suitable for high-purity water after MRS System

Proper pre-treatment is required to control MR cartridge (membrane) scale formation and/or fouling

Raw water hardness in excess of seven (7) grains per gallon should be softened to extend cartridge life

The raw water may contain chlorine or other oxidizers and the use of a carbon pre-filter is recommended

OPERATION TIPS

Change MR cartridge on a regular preventative maintenance program

Change MR cartridge when output capacity diminishes by 15%, or when output pressure becomes too low

Always flush the MR cartridge at time of installation and cartridge change

Contact Pentair Technical Service for pre-treatment recommendations

Refer to Installation, Operation & Maintenance manual for cartridge flushing and RO startup

SIZING

Rated Capacity: 600 gallons per day (2,271 Liters per day) Nominal. Water pressure, feedwater quality and temperature will effect actual daily production rate

Service Flow Rate: Dependant on water volume and pressure in storage tank(s), and line size(s) to equipment

EVERPURE® MR-600 REPLACEMENT CARTRIDGE

EV9627-13



SPECIFICATIONS

Overall Dimensions

25" L x 3.25" dia. (63.5 x 8.3 cm)

Rated Capacity

600 gallons per day (2,271 Liters per day) Nominal. Water pressure, feedwater quality and temperature will effect actual daily production rate

Service Flow Rate

Dependant on water volume and pressure in storage tank(s), and line size(s) to equipment

Pressure Requirements

40 - 100 psi (2.7 - 6.8 bar), non-shock

Temperature

35 - 100°F (2 - 38°C)

Inlet TDS

1,000 ppm max recommended

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

WARRANTY

Everpure water treatment systems by Pentair® (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Pentair will provide a copy of the warranty upon request.



FILTRATION & PROCESSING SOLUTIONS

EVERPURE-SHURFLO WORLD HEADQUARTERS, 1040 MUIRFIELD DRIVE, HANOVER PARK, IL 60133 USA • WWW.EVERPURE.COM 800.942.1153 MAIN (US ONLY) • 630.307.3000 MAIN • 630.307.3030 FAX • CSEVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO AUSTRALIA / NEW ZEALAND, 1-21 MONASH DRIVE, DANDENONG SOUTH, VIC, 3175, AUSTRALIA 1300.576.190 TEL • AU.EVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO CHINA, 21F CLOUD 9 PLAZA, NO 1118, SHANGHAI, 200052, CHINA 86.21.3211.4588 TEL • 86.21.3211.4580 FAX • CHINA.WATER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO INDIA, GREEN BOULEVARD, B-9/A, 7TH FLOOR - TOWER B SECTOR 62, NOIDA - 201301

91.120.419.9444 TEL • 91.120.419.9400 FAX • INDIACUSTOMER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO EUROPE, PENTAIR WATER BELGIUM BVBA, INDUSTRIEPARK WOLFSTEE, TOEKOMSTLAAN, 30 B-2200 HERENTALS, BELGIUM +32.(0).14.283.500 TEL • +32.(0).14.283.505 FAX • SALES@EVERPURE-EUROPE.COM EMAIL

EVERPURE-SHURFLO JAPAN INC., HASHIMOTO MN BLDG. 7F, 3-25-1 HASHIMOTO, MIDORI-KU, SAGAMIHARA-SHI KANAGAWA 252-0143, JAPAN 81.(0)42.775.3011 TEL • 81.(0)42.775.3015 FAX • INFO@EVERPURE.CO.JP EMAIL

EVERPURE-SHURFLO SOUTHEAST ASIA, 390 HAVELOCK ROAD, #04-01 KING'S CENTRE, SINGAPORE 169662, 65.6768.5800 TEL • 65.6737.5149 FAX • EMAIL CSEVERPURE@PENTAIR.COM EMAIL

All Pentair trademarks and logos are owned by Pentair, Inc. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

© 2014 Pentair Filtration Solutions, LLC EV9627-13 MR14